

# Crystal Tourniket



**Completely constructed from glass with only the most minimal stainless steel frame and cappings, the Crystal Tourniket is the most transparent revolving door available. Despite its transparency however, it makes a striking entry to any building. It is available with three or four door wings and with manual or automatic operation.**

#### **Options**

- Low torque drive unit with Speed Control
- Push-button temporary low speed
- Safety Plus Package for applications where a higher level of safety is required
- Power assist, Positioning Speed Control (PPS) for manual doors
- Push & Go or motion detection start up
- Idle speed
- Direction sensitive motion detectors
- Stainless steel soffit
- Coloured interlayer to glass soffit, curved walls and night locking doors
- Roof trim
- Floor mats
- Teleboon remote monitoring

#### **Night Locking Options**




- Night locking doors
- Mechanical lock (door wing)





## Dimensions and Specifications

A Diameter (mm)	Capacity / Minute	# of Door Wings	Disabled Access	Type of Traffic	Emergency Exit	B Instal- lation Width (mm)	C Throat Opening (mm)	D Height Under Canopy (mm)	E Soffit Height (mm)
1600	2x 22	3	x		x	1650	719	2100-3000	18
1600	2x 26	4	x		x	1650	1069	2100-3000	18
1800	2x 22	3	x		x	1850	819	2100-3000	18
1800	2x 26	4	x		x	1850	1211	2100-3000	18
2000	2x 22	3	x		x	2050	919	2100-3000	18
2000	2x 26	4	x		x	2050	1352	2100-3000	18
2200	2x 20	3	x		x	2250	1019	2100-3000	18
2200	2x 26	4	x		x	2250	1494	2100-3000	18
2400	2x 18	3	x		x	2450	1119	2100-3000	18
2400	2x 24	4	x		x	2450	1635	2100-3000	18
2600	2x 33	3	x		x	2650	1219	2100-3000	18
2600	2x 22	4	x		x	2650	1777	2100-3000	18
2800	2x 31	3	x		x	2850	1319	2100-3000	18
2800	2x 20	4	x		x	2850	1918	2100-3000	18
3000	2x 29	3	x		x	3050	1419	2100-3000	18
3000	2x 38	4	x		x	3050	2060	2100-3000	18



## Technical Specifications

Power Supply: 200-240 VAC, 50/60 Hz

Motor: AC motor, 3-phase

### Power Consumption

Operating: 150W

Stationary: 75W

Ambient Temperature: -20°C to +50°C

Fuse: External Power supply fused with 16A slow



# Find Out More

**If you have a question regarding the Crystal Tourniket, please complete the below form and one of our experts will contact you within one business day.**

Name

Company Name

Email

Telephone

Message

SUBMIT